



TIMBERWOLF®
Lead the Pack

TW 230VTR

6" TRACKED PETROL WOOD CHIPPER



- 6 1/3" (160mm) cutting performance
- High power B&S Vanguard V twin petrol engine
- WolfTrack® variable width, dual speed tracking system



01449 765800

timberwolf-uk.com

f @mytimberwolf

TW 230VTR



TIMBERWOLF®
Lead the Pack

FEATURES AND SPECIFICATIONS

FEATURES

- Stage V compliant
- Class-leading 230mm x 160mm feed opening
- Up to 5 tonnes per hour
- Minimum width of 810mm
- 280° adjustable discharge
- Average chip size 18mm
- Optional winch




Non Latching Reverse Feed Control
Ultimate control and safety with large positive feedback buttons.



Quad Force Rollers
Horizontal hydraulic rollers for ultimate grip, crushing and infeed power.



Exhaust-Gas Diffuser
(Patent Pending)
Reduces exhaust gas temperature by up to 150°C for a safer working environment.



WolfTrack®
Variable width, dual speed tracking system with a minimum width of 810mm.



WolfPort
Quick & easy access to the blades and rotor housing.



Reversible Blades
Unique double half-cut chipping system with double sided, hollow ground blades - exceptional cutting performance, processing.

| ENGINE | FUEL | TANK CAPACITY | WEIGHT | LENGTH TRAY UP/ TRAY DOWN | WIDTH | HEIGHT | MAXIMUM DIAMETER INFEE | THROUGH-PUT | FEED METHOD | BLADES |
|--------------------------|--------|-------------------------|--------|---------------------------|--------------|--------|------------------------|-------------------------|--|---|
| 37hp Briggs and Stratton | Petrol | 36 litres (7.9 gallons) | 1172kg | 2725mm 3460mm | 810mm 1300mm | 2225mm | 160mm (6 1/8") | Up to 5 tonnes per hour | Twin hydraulic rollers c/w Auto Feed Control | 2 x 135mm (5 1/4") double sided, fully hardened |

01449 765800

timberwolf-uk.com

f @mytimberwolf